



Machinery Parts Co., Ltd.

7HR2555T+[148-2600/1]L[H,P,SP,UP] THK Separated Linear Guide Side Rails Set Model HR

Bearing No. 7HR2555T+[148-2600/1]L[H,P,SP,UP]

Days to Ship	42 Days
Rail Width W1	22 mm
Mounting Height M	25 mm
Number of blocks	7
Material	Carbon Steel
Rail Length L	148 ~ 2600 mm
Accuracy Grade	High Grade / Precision Grade / High Precision Grade / Extra High Precision Grade
Callout Size	2555
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	25100
Basic Load Rating Static Rating Co(N)	40800
Allowable static moment MA(N · m)	1330
Allowable static moment MB(N · m)	1330
The outside dimension W of block	33.3 mm
The outside dimension L of block	146.4 mm
Mounting Hole Dimension S(M)	M8
The dimension L1 of blocks	105.4 mm
LM Block Surface	Not Provided

7HR2555T+[148-2600/1]L[H,P,SP,UP] Bearing
2D drawings and 3D CAD models



Machinery Parts Co., Ltd.

Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	
LM Rail Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	Not Provided