



Machinery Parts Co., Ltd.

5SRS15WM+[57-1000/1]L[H,P]M THK Miniature Linear Guide Caged Ball SRS Series

Bearing No. 5SRS15WM+[57-1000/1]L[H,P]M

Days to Ship	3 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	5
Nominal Part Number	15W
Rail Type	Wide Rail
Rail Width W1	42 mm
Mounting Height M	16 mm
Rail Length L	57 ~ 1000 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	9120
Basic Load Rating Static Rating Co(N)	8550
Allowable Static Moment MA(N m)	51.2
Allowable Static Moment MB(N m)	51.2
Allowable Static Moment MC(N m)	176
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	60 mm
Block external dimension L	55.5 mm
Number of Block Mounting	4

5SRS15WM+[57-1000/1]L[H,P]M Bearing 2D
drawings and 3D CAD models



Machinery Parts Co., Ltd.

Holes(holes)	
Mounting Hole Dimension S(M)	M4
Mounting Hole Screw Depth	4.5 mm
Block dimension L1	38.9 mm