



# Machinery Parts Co., Ltd.

## 5SRS15WGN[SS,SSHH,UU]C1+[76-900/1] LM THK Miniature Linear Guide Full Ball SRS-G Accuracy and Preload Selectable

Bearing No. 5SRS15WGN[SS,SSHH,UU]C1+[76-900/1]LM

5SRS15WGN[SS,SSHH,UU]C1+[76-900/1]LM  
Bearing 2D drawings and 3D CAD models

Days to Ship	22 Days
Block Type	[Long] N: Long
The number of LM blocks combined with a axis	5
Nominal Part Number	15W
Rail Type	Wide Rail
Rail Width W1	42 mm
Mounting Height M	16 mm
Rail Length L	76 ~ 900 mm
Radial Clearance	Light Preload
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	9870
Basic Load Rating Static Rating Co(N)	15300
Allowable Static Moment MA(N m)	133
Allowable Static Moment MB(N m)	133
Allowable Static Moment MC(N m)	317
Symbols for Dust Resistance	UU: End Seals
Advanced Seal Options (Longer Leadtime)	SSHH: SS + Laminated Contact Scraper LaCS



## Machinery Parts Co., Ltd.

Block external dimension W	16 mm
Block external dimension L	74.5 mm
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M4
Mounting Hole Screw Depth	4.5 mm
Block dimension L1	57.9 mm